Algorithms & Models of Computation CS/ECE 374, Fall 2020

7.6

CFGs normal form

Normal forms are a way to restrict form of production rules

Advantage: Simpler/more convenient algorithms and proofs

Two standard normal forms for CFGs

- Chomsky normal form
- Greibach normal form

Normal forms are a way to restrict form of production rules

Advantage: Simpler/more convenient algorithms and proofs

Two standard normal forms for CFGs

- Chomsky normal form
- Greibach normal form

Chomsky Normal Form:

- Productions are all of the form $A \to BC$ or $A \to a$. If $\epsilon \in L$ then $S \to \epsilon$ is also allowed.
- Every CFG G can be converted into CNF form via an efficient algorithm
- Advantage: parse tree of constant degree.

Greibach Normal Form:

- ullet Only productions of the form A o aeta are allowed.
- ullet All CFLs without ϵ have a grammar in GNF. Efficient algorithm.
- Advantage: Every derivation adds exactly one terminal.

Chomsky Normal Form:

- Productions are all of the form $A \to BC$ or $A \to a$. If $\epsilon \in L$ then $S \to \epsilon$ is also allowed.
- Every CFG G can be converted into CNF form via an efficient algorithm
- Advantage: parse tree of constant degree.

Greibach Normal Form:

- Only productions of the form $A \rightarrow a\beta$ are allowed.
- ullet All CFLs without ϵ have a grammar in GNF. Efficient algorithm.
- Advantage: Every derivation adds exactly one terminal.

THE END

. . .

(for now)