


Announcements

Thanks for being a great class!



Join Code: **225**






BTree Introduction

Learning Objectives

1. Understand the motivation behind BTrees
2. Know all the BTree Properties
3. Understand how to insert elements into a BTree
4. Implement Search in a BTree




AVL Trees



Rate Limiting Factor - Seeks

Distributed Databases

Hard Disks



System Design


Goal: Minimize the number of reads!

Build a tree that uses _____ / node

1. Distributed Database - [1 network packet]
 - a. 1500 Bytes (1 MTU) (Maximum Transmissible Unit)
2. Hard Disk - [1 disk block]
 - a. Old Systems 512 Bytes
 - b. New Systems 4096 Bytes



What are some observations about B-Trees?



BTree Properties

A **BTree**s of order **m** is an m-way tree:

Definition

- All keys within a node are ordered
- All nodes contain no more than **m-1** keys
- All internal nodes have **one more child than keys**
- All leaves are on the same level



B-Tree Operations

Insert



Find

Remove - More complicated, there is a POTD about this, not discussed in this class




Insert - Recursive Split

Insert(17)




What will be the root after insert(5)? Assume $m = 3$




Join Code: 225

What will be the root after insert(5)? Assume $m = 3$



What will be the root after insert(5)? Assume $m = 3$



B-Tree Insert

- Always inserts at leaf level
- Split if m nodes are reached
- Split could propagate up the tree recursively



BTree Properties

A **BTree** of order **m** is an m-way tree:

Definition


- All keys within a node are ordered
- All nodes contain no more than **m-1** keys
- All internal nodes have **one more child than keys**
- All leaves are on the same level
- Root node is a leaf or has **[2, m]** children.
- All non-root, internal nodes have **[ceil(m/2), m]** children




If this is a valid BTree, what is the lower bound for m?




Join Code: 225



If this is a valid BTree, what is the upper bound for m ?



B-Tree Find: How would find(12) work? find(54)?



BTree Search

```
1 template <typename K, typename V>
2 V BTree<K, V>::_find(BTreeNode * node, const K & key) const {
3     unsigned i;
4     for (i = 0; i < node.keys_ct_ && key > node.keys_[i]; i++) { }
5
6     if (i < node.keys_ct_ && key == node.keys_[i]) {
7         return node.values_[i];
8     }
9
10    if (node.isLeaf()) {
11        return V();
12    }
13
14    BTreeNode nextChild = node._fetchChild(i);
15    return _find(nextChild, key);
16 }
```

BTree Properties

A **BTree** of order **m** is an m-way tree:

Definition

- All keys within a node are ordered
- All nodes contain no more than **m-1** keys
- All internal nodes have **one more child than keys**
- All leaves are on the same level
- Root node is a leaf or has **[2, m]** children.
- All non-root, internal nodes have **[ceil(m/2), m]** children

