

Here are several problems that are easy to solve in $O(n)$ time, essentially by brute force. Your task is to design algorithms for these problems that are significantly faster.

1. Suppose we are given an array $A[1..n]$ of n distinct integers, which could be positive, negative, or zero, sorted in increasing order so that $A[1] < A[2] < \dots < A[n]$.
 - (a) Describe a fast algorithm that either computes an index i such that $A[i] = i$ or correctly reports that no such index exists.

Solution: Suppose we define a second array $B[1..n]$ by setting $B[i] = A[i] - i$ for all i . For every index i we have

$$B[i] = A[i] - i \leq (A[i+1] - 1) - i = A[i+1] - (i+1) = B[i+1],$$

so this new array is sorted in increasing order. Clearly, $A[i] = i$ if and only if $B[i] = 0$. So we can find an index i such that $A[i] = i$ by performing a binary search in B . We don't actually need to compute B in advance; instead, whenever the binary search needs to access some value $B[i]$, we can just compute $A[i] - i$ on the fly instead!

Here are two formulations of the resulting algorithm, first recursive (keeping the array A as a global variable), and second iterative.

```

  <<Return any index  $i$  such that  $\ell \leq i \leq r$  and  $A[i] = i$ >>
  FINDMATCH( $\ell, r$ ):
    if  $\ell > r$ 
      return NONE
     $mid \leftarrow (\ell + r)/2$ 
    if  $A[mid] = mid$                                 << $B[mid] = 0$ >>
      return  $mid$ 
    else if  $A[mid] < mid$                             << $B[mid] < 0$ >>
      return FINDMATCH( $mid + 1, r$ )
    else                                             << $B[mid] > 0$ >>
      return FINDMATCH( $\ell, mid - 1$ )

```

```

  FINDMATCH( $A[1..n]$ ):
     $hi \leftarrow n$ 
     $lo \leftarrow 1$ 
    while  $lo \leq hi$ 
       $mid \leftarrow (lo + hi)/2$ 
      if  $A[mid] = mid$                                 << $B[mid] = 0$ >>
        return  $mid$ 
      else if  $A[mid] < mid$                             << $B[mid] < 0$ >>
         $lo \leftarrow mid + 1$ 
      else                                             << $B[mid] > 0$ >>
         $hi \leftarrow mid - 1$ 
    return NONE

```

In both formulations, the algorithm *is* binary search, so it runs in $O(\log n)$ time. ■

- (b) Suppose we know in advance that $A[1] > 0$. Describe an even faster algorithm that either computes an index i such that $A[i] = i$ or correctly reports that no such index exists. [Hint: This is *really* easy.]

Solution: The following algorithm solves this problem in $O(1)$ time:

```
FINDMATCHPOS(A[1..n]):  
  if A[1] = 1  
    return 1  
  else  
    return NONE
```

Again, the array $B[1..n]$ defined by setting $B[i] = A[i] - i$ is sorted in increasing order. It follows that if $A[1] > 1$ (that is, $B[1] > 0$), then $A[i] > i$ (that is, $B[i] > 0$) for every index i . $A[1]$ cannot be less than 1. ■

2. Suppose we are given an array $A[1..n]$ such that $A[1] \geq A[2]$ and $A[n-1] \leq A[n]$. We say that an element $A[x]$ is a **local minimum** if both $A[x-1] \geq A[x]$ and $A[x] \leq A[x+1]$. For example, there are exactly six local minima in the following array:

9	7	7	2	1	3	7	5	4	7	3	3	4	8	6	9
	▲			▲				▲		▲	▲			▲	

Describe and analyze a fast algorithm that returns the index of one local minimum. For example, given the array above, your algorithm could return the integer 9, because $A[9]$ is a local minimum. [Hint: With the given boundary conditions, any array **must** contain at least one local minimum. Why?]

Solution: The following algorithm solves this problem in $O(\log n)$ time:

```

LOCALMIN( $A[1..n]$ ):
  if  $n < 100$ 
    find the smallest element in  $A$  by brute force
   $m \leftarrow \lfloor n/2 \rfloor$ 
  if  $A[m] < A[m+1]$ 
    return LOCALMIN( $A[1..m+1]$ )
  else
    return LOCALMIN( $A[m..n]$ )

```

If n is less than 100, then a brute-force search runs in $O(1)$ time. There's nothing special about 100 here; any other constant will do.

Otherwise, if $A[\lfloor n/2 \rfloor] < A[\lfloor n/2 \rfloor + 1]$, the subarray $A[1.. \lfloor n/2 \rfloor + 1]$ satisfies the precise boundary conditions of the original problem, so the recursion fairy will find local minimum inside that subarray.

Finally, if $A[\lfloor n/2 \rfloor] > A[\lfloor n/2 \rfloor + 1]$, the subarray $A[\lfloor n/2 \rfloor .. n]$ satisfies the precise boundary conditions of the original problem, so the recursion fairy will find local minimum inside that subarray.

The running time satisfies the recurrence $T(n) \leq T(\lfloor n/2 \rfloor + 1) + O(1)$. Except for the $+1$ and the ceiling in the recursive argument, which we can ignore, this is the binary search recurrence, whose solution is $T(n) = O(\log n)$.

Alternatively, we can observe that $\lfloor n/2 \rfloor + 1 < 2n/3$ when $n \geq 100$, and therefore $T(n) \leq T(2n/3) + O(1)$, which implies $T(n) = O(\log_{3/2} n) = O(\log n)$. ■

3. Suppose you are given two sorted arrays $A[1..n]$ and $B[1..n]$ containing distinct integers. Describe a fast algorithm to find the median (meaning the n th smallest element) of the union $A \cup B$. For example, given the input

$$A[1..8] = [0, 1, 6, 9, 12, 13, 18, 20] \quad B[1..8] = [2, 4, 5, 8, 17, 19, 21, 23]$$

your algorithm should return the integer 9. [Hint: What can you learn by comparing one element of A with one element of B ?]

Solution: The following algorithm solves this problem in $O(\log n)$ time:

```

MEDIAN(A[1..n], B[1..n]) :
  if n < 10100
    use brute force
  else if A[n/2] > B[n/2]
    return MEDIAN(A[1..n/2], B[n/2 + 1..n])
  else
    return MEDIAN(A[n/2 + 1..n], B[1..n/2])

```

Suppose $A[n/2] > B[n/2]$. Then $A[n/2 + 1]$ is larger than all n elements in $A[1..n/2] \cup B[1..n/2]$, and therefore larger than the median of $A \cup B$, so we can discard the upper half of A . Similarly, $B[n/2 - 1]$ is smaller than all $n + 1$ elements of $A[n/2..n] \cup B[n/2 + 1..n]$, and therefore smaller than the median of $A \cup B$, so we can discard the lower half of B . Because we discard the same number of elements from each array, the median of the remaining subarrays is the median of the original $A \cup B$. ■

To think about later:

4. Now suppose you are given two sorted arrays $A[1..m]$ and $B[1..n]$ and an integer k . Describe a fast algorithm to find the k th smallest element in the union $A \cup B$. For example, given the input

$$A[1..8] = [0, 1, 6, 9, 12, 13, 18, 20] \quad B[1..5] = [2, 5, 7, 17, 19] \quad k = 6$$

your algorithm should return the integer 7.

Solution: The following algorithm solves this problem in $O(\log \min\{k, m + n - k\}) = O(\log(m + n))$ time:

```

SELECT(A[1..m], B[1..n], k) :
  if k < (m + n)/2
    return MEDIAN(A[1..k], B[1..k])
  else
    return MEDIAN(A[k - n..m], B[k - m..n])

```

Here, `MEDIAN` is the algorithm from problem 3 with one minor tweak. If `MEDIAN` wants an entry in either A or B that is outside the bounds of the original arrays, it uses the value $-\infty$ if the index is too low, or ∞ if the index is too high, instead of creating a core dump ■