A ***subsequence*** of a sequence (for example, an array, a linked list, or a string), obtained by removing zero or more elements and keeping the rest in the same sequence order. A subsequence is called a ***substring*** if its elements are contiguous in the original sequence. For example:

- `SUBSEQUENCE`, `UBSEQU`, and the empty string ε are all substrings of `SUBSEQUENCE`;
- `SBSQNC`, `UEQUE`, and `EEE` are all subsequences of `SUBSEQUENCE` but not substrings;
- `QUEUE`, `SSS`, and `FOOBAR` are not subsequences of `SUBSEQUENCE`.

Describe and analyze ***dynamic programming*** algorithms for the following longest-subsequence problems. Use the recurrences you developed on Wednesday.

The second page of this handout includes detailed steps on how you should develop dynamic programming algorithms.

1. Given an array $A[1..n]$ of integers, compute the length of a longest ***decreasing*** subsequence of A. A sequence $B[1..\ell]$ is *decreasing* if $B[i] < B[i-1]$ for every index $i \geq 2$.

2. Given an array $A[1..n]$ of integers, compute the length of a longest ***alternating*** subsequence of A. A sequence $B[1..\ell]$ is *alternating* if $B[i] < B[i-1]$ for every even index $i \geq 2$, and $B[i] > B[i-1]$ for every odd index $i \geq 3$.

3. Given an array $A[1..n]$ of integers, compute the length of a longest ***convex*** subsequence of A. A sequence $B[1..\ell]$ is *convex* if $B[i]-B[i-1] > B[i-1]-B[i-2]$ for every index $i \geq 3$.

4. Given an array $A[1..n]$, compute the length of a longest ***palindrome*** subsequence of A. Recall that a sequence $B[1..\ell]$ is a *palindrome* if $B[i] = B[\ell - i + 1]$ for every index i.

5. Given an array $A[1..n]$, compute the length of a ***shortest*** palindrome ***supersequence*** of A. Sequence B is a *supersequence* of another sequence C if and only if C is a subsequence of B.

Basic steps in developing a dynamic programming algorithm

1. **Formulate the problem recursively.** This is the hard part. There are two distinct but equally important things to include in your formulation.

   (a) **Specification.** First, give a clear and precise English description of the problem you are claiming to solve. Not *how* to solve the problem, but *what* the problem actually is. **Omitting this step in homeworks or exams may cost you all points for the problem!**

   (b) **Solution.** Second, give a clear recursive formula or algorithm for the whole problem in terms of the answers to smaller instances of *exactly* the same problem. It generally helps to think in terms of a recursive definition of your inputs and outputs. If you discover that you need a solution to a *similar* problem, or a slightly *related* problem, you're attacking the wrong problem; go back to step 1.

   (c) **Don't optimize prematurely.** It may be tempting to ignore "obviously" suboptimal choices, because that will yield an "obviously" faster algorithm, but it's usually a bad idea, for two reasons. First, the optimization may not actually improve the running time of the final dynamic programming algorithm. But more importantly, many "obvious" optimizations are actually incorrect! ***First* make it work; *then* optimize.**

2. **Build solutions to your recurrence from the bottom up.** Write an algorithm that starts with the base cases of your recurrence and works its way up to the final solution, by considering intermediate subproblems in the correct order.

   (a) **Identify the subproblems.** What are all the different ways can your recursive algorithm call itself, starting with some initial input?

   (b) **Analyze running time.** Add up the running times of all possible subproblems, *ignoring the recursive calls*.

   (c) **Choose a memoization data structure.** For most problems, each recursive subproblem can be identified by a few integers, so you can use a multidimensional array. But some problems need a more complicated data structure.

   (d) **Identify dependencies.** Except for the base cases, every recursive subproblem depends on other subproblems—which ones? Draw a picture of your data structure, pick a generic element, and draw arrows from each of the other elements it depends on. Then formalize your picture.

   (e) **Find a good evaluation order.** Order the subproblems so that each subproblem comes *after* the subproblems it depends on. Typically, you should consider the base cases first, then the subproblems that depends only on base cases, and so on. ***Be careful!***

   (f) **Write down the algorithm.** You know what order to consider the subproblems, and you know how to solve each subproblem. So do that! If your data structure is an array, this usually means writing a few nested for-loops around your original recurrence.

3. **Try to improve.** What's the bottleneck in your algorithm? Can you find a faster algorithm by modifying the recurrence? Can you tighten the time analysis? *Now* is the time to think

about removing "obviously" redundant or suboptimal choices. (But always make sure that your optimizations are correct!!)