

Programming Languages and Compilers (CS 421)

Elsa L Gunter
2112 SC, UIUC

<http://courses.engr.illinois.edu/cs421>

Based in part on slides by Mattox Beckman, as updated by Vikram Adve and Gul Agha

10/26/23

1

Example of Failure: Decompose

- Unify $\{(f(x,g(y)) = f(h(y),x))\}$
- Decompose: $(f(x,g(y)) = f(h(y),x))$
- = Unify $\{(x = h(y)), (g(y) = x)\}$
- Orient: $(g(y) = x)$
- = Unify $\{(x = h(y)), (x = g(y))\}$
- Eliminate: $(x = h(y))$
- Unify $\{(h(y) = g(y))\} \circ \{x \rightarrow h(y)\}$
- No rule to apply! Decompose fails!

10/26/23

2

Example of Failure: Occurs Check


- Unify $\{(f(x,g(x)) = f(h(x),x))\}$
- Decompose: $(f(x,g(x)) = f(h(x),x))$
- = Unify $\{(x = h(x)), (g(x) = x)\}$
- Orient: $(g(x) = x)$
- = Unify $\{(x = h(x)), (x = g(x))\}$
- No rules apply.

10/26/23

3

Programming Languages & Compilers

Three Main Topics of the Course




10/26/23

4

Programming Languages & Compilers


II : Language Translation



10/26/23

5

Major Phases of a Compiler



Modified from "Modern Compiler Implementation in ML", by Andrew Appel

Where We Are Going Next?

- We want to turn strings (code) into computer instructions
- Done in phases
- Turn strings into abstract syntax trees (parse)
- Translate abstract syntax trees into executable instructions (interpret or compile)

10/26/23

7

Meta-discourse

- Language Syntax and Semantics
- Syntax
 - Regular Expressions, DFSAs and NDFSAs
 - Grammars
- Semantics
 - Natural Semantics
 - Transition Semantics

10/26/23

8

Language Syntax

- Syntax is the description of which strings of symbols are meaningful expressions in a language
- It takes more than syntax to understand a language; need meaning (semantics) too
- Syntax is the entry point

10/26/23

9

Syntax of English Language

- Pattern 1

Subject	Verb
David	sings
The dog	barked
Susan	yawned

- Pattern 2

Subject	Verb	Direct Object
David	sings	ballads
The professor	wants	to retire
The jury	found	the defendant guilty

10/26/23

10

Elements of Syntax

- Character set – previously always ASCII, now often 64 character sets
- Keywords – usually reserved
- Special constants – cannot be assigned to
- Identifiers – can be assigned to
- Operator symbols
- Delimiters (parenthesis, braces, brackets)
- Blanks (aka white space)

10/26/23

11

Elements of Syntax

- Expressions
 - if ... then begin ... ; ... end else begin ... ; ... end
- Type expressions
 - $type_{expr_1} \rightarrow type_{expr_2}$
- Declarations (in functional languages)
 - let *pattern* = *expr*
- Statements (in imperative languages)
 - $a = b + c$
- Subprograms
 - let *pattern*₁ = *expr*₁ in *expr*

10/26/23

12

Elements of Syntax

- Modules
- Interfaces
- Classes (for object-oriented languages)

10/26/23

13

Lexing and Parsing

- Converting strings to abstract syntax trees done in two phases
 - **Lexing:** Converting string (or streams of characters) into lists (or streams) of tokens (the “words” of the language)
 - Specification Technique: Regular Expressions
 - **Parsing:** Convert a list of tokens into an abstract syntax tree
 - Specification Technique: BNF Grammars

10/26/23

14

Formal Language Descriptions

- Regular expressions, regular grammars, finite state automata
- Context-free grammars, BNF grammars, syntax diagrams
- Whole family more of grammars and automata – covered in automata theory

10/26/23

15

Grammars

- Grammars are formal descriptions of which strings over a given character set are in a particular language
- Language designers write grammar
- Language implementers use grammar to know what programs to accept
- Language users use grammar to know how to write legitimate programs

10/26/23

16

Regular Expressions - Review

- Start with a given character set – **a, b, c...**
- $L(\epsilon) = \{""\}$
- Each character is a regular expression
 - It represents the set of one string containing just that character
 - $L(a) = \{a\}$

10/26/23

17

Regular Expressions

- If **x** and **y** are regular expressions, then **xy** is a regular expression
 - It represents the set of all strings made from first a string described by **x** then a string described by **y**
- If $L(x) = \{a, ab\}$ and $L(y) = \{c, d\}$
then $L(xy) = \{ac, ad, abc, abd\}$

10/26/23

18

Regular Expressions

- If x and y are regular expressions, then $x \vee y$ is a regular expression
 - It represents the set of strings described by either x or y
 - If $L(x) = \{a, ab\}$ and $L(y) = \{c, d\}$ then $L(x \vee y) = \{a, ab, c, d\}$

10/26/23

19

Regular Expressions

- If x is a regular expression, then so is (x)
 - It represents the same thing as x
- If x is a regular expression, then so is x^*
 - It represents strings made from concatenating zero or more strings from x
 - If $L(x) = \{a, ab\}$ then $L(x^*) = \{\epsilon, a, ab, aa, aab, abab, \dots\}$
- ϵ
 - It represents $\{\epsilon\}$, set containing the empty string
- \emptyset
 - It represents $\{\}$, the empty set

10/26/23

20

Example Regular Expressions

- $(0 \vee 1)^* 1$
 - The set of all strings of 0's and 1's ending in 1, $\{1, 01, 11, \dots\}$
- $a^* b (a^*)$
 - The set of all strings of a's and b's with exactly one b
- $((01) \vee (10))^*$
 - You tell me
- Regular expressions (equivalently, regular grammars) important for lexing, breaking strings into recognized words

10/26/23

21

Right Regular Grammars

- Subclass of BNF (covered in detail sool)
- Only rules of form
 - $\langle \text{nonterminal} \rangle ::= \langle \text{terminal} \rangle \langle \text{nonterminal} \rangle$ or
 - $\langle \text{nonterminal} \rangle ::= \langle \text{terminal} \rangle$ or
 - $\langle \text{nonterminal} \rangle ::= \epsilon$
- Defines same class of languages as regular expressions
- Important for writing lexers (programs that convert strings of characters into strings of tokens)
- Close connection to nondeterministic finite state automata – nonterminals \cong states; rule \cong edge

10/26/23

22

Example

- Right regular grammar:
 - $\langle \text{Balanced} \rangle ::= \epsilon$
 - $\langle \text{Balanced} \rangle ::= 0 \langle \text{OneAndMore} \rangle$
 - $\langle \text{Balanced} \rangle ::= 1 \langle \text{ZeroAndMore} \rangle$
 - $\langle \text{OneAndMore} \rangle ::= 1 \langle \text{Balanced} \rangle$
 - $\langle \text{ZeroAndMore} \rangle ::= 0 \langle \text{Balanced} \rangle$
- Generates even length strings where every initial substring of even length has same number of 0's as 1's

10/26/23

23

Implementing Regular Expressions

- Regular expressions reasonable way to generate strings in language
- Not so good for recognizing when a string is in language
- Problems with Regular Expressions
 - which option to choose,
 - how many repetitions to make
- Answer: finite state automata
- Should have seen in CS374

10/26/23

24

Example: Lexing

- Regular expressions good for describing lexemes (words) in a programming language
 - Identifier = $(a \vee b \vee \dots \vee z \vee A \vee B \vee \dots \vee Z) (a \vee b \vee \dots \vee z \vee A \vee B \vee \dots \vee Z \vee 0 \vee 1 \vee \dots \vee 9)^*$
 - Digit = $(0 \vee 1 \vee \dots \vee 9)$
 - Number = $0 \vee (1 \vee \dots \vee 9)(0 \vee \dots \vee 9)^* \vee \sim (1 \vee \dots \vee 9)(0 \vee \dots \vee 9)^*$
 - Keywords: if = if, while = while,...

10/26/23

25

Lexing

- Different syntactic categories of “words”: tokens
- Example:
- Convert sequence of characters into sequence of strings, integers, and floating point numbers.
 - "asd 123 jkl 3.14" will become:
[String "asd"; Int 123; String "jkl"; Float 3.14]

10/26/23

26

Lex, ocamllex

- Could write the reg exp, then translate to DFA by hand
 - A lot of work
- Better: Write program to take reg exp as input and automatically generates automata
- Lex is such a program
- ocamllex version for ocaml

10/26/23

27

How to do it

- To use regular expressions to parse our input we need:
 - Some way to identify the input string — call it a lexing buffer
 - Set of regular expressions,
 - Corresponding set of actions to take when they are matched.

10/26/23

28

How to do it

- The lexer will take the regular expressions and generate a state machine.
- The state machine will take our lexing buffer and apply the transitions...
- If we reach an accepting state from which we can go no further, the machine will perform the appropriate action.

10/26/23

29

Mechanics

- Put table of reg exp and corresponding actions (written in ocaml) into a file `<filename>.mll`
- Call


```
ocamllex <filename>.mll
```
- Produces Ocaml code for a lexical analyzer in file `<filename>.ml`

10/26/23

30

Sample Input

```
rule main = parse
  ['0'-'9']+ { print_string "Int\n"}
  | ['0'-'9']+.'['0'-'9']+ { print_string "Float\n"}
  | ['a'-'z']+ { print_string "String\n"}
  | _ { main lexbuf }
{
  let newlexbuf = (Lexing.from_channel stdin) in
  main newlexbuf
}
```

10/26/23

31

General Input

```
{ header }
let ident = regexp ...
rule entrypoint [arg1... argn] = parse
  regexp { action }
  | ...
  | regexp { action }
and entrypoint [arg1... argn] = parse ...and
...
{ trailer }
```

10/26/23

32

Ocamllex Input

- *header* and *trailer* contain arbitrary ocaml code put at top and bottom of *<filename>.ml*
- `let ident = regexp ...` Introduces *ident* for use in later regular expressions

10/26/23

33

Ocamllex Input

- *<filename>.ml* contains one lexing function per *entrypoint*
 - Name of function is name given for *entrypoint*
 - Each entry point becomes an Ocaml function that takes $n+1$ arguments, the extra implicit last argument being of type `Lexing.lexbuf`
- *arg1... argn* are for use in *action*

10/26/23

34

Ocamllex Regular Expression

- Single quoted characters for letters:
 - `'a'`
- `_`: (underscore) matches any letter
- `Eof`: special "end_of_file" marker
- Concatenation same as usual
- `"string"`: concatenation of sequence of characters
- e_1 / e_2 : choice - what was $e_1 \vee e_2$

10/26/23

35

Ocamllex Regular Expression

- $[c_1 - c_2]$: choice of any character between first and second inclusive, as determined by character codes
- $[^c_1 - c_2]$: choice of any character NOT in set
- e^* : same as before
- $e+$: same as $e e^*$
- $e?$: option - was $e \vee \epsilon$
- (e) : same as e

10/26/23

36

Ocamllex Regular Expression

- $e_1 \# e_2$: the characters in e_1 but not in e_2 ; e_1 and e_2 must describe just sets of characters
- *ident*: abbreviation for earlier reg exp in `let ident = regexp`
- e_1 as *id*: binds the result of e_1 to *id* to be used in the associated *action*

10/26/23

37

Ocamllex Manual

More details can be found at
Version for ocaml 4.07:
<https://v2.ocaml.org/releases/4.07/htmlman/lex yacc.html>

Current version (ocaml 4.14)
<https://v2.ocaml.org/releases/4.14/htmlman/lex yacc.html>
(same, except formatting, I think)

10/26/23

38

End of Lect 18

10/26/23

39

Example : test.mll

```
{ type result = Int of int | Float of float |  
  String of string }  
let digit = ['0'-'9']  
let digits = digit +  
let lower_case = ['a'-'z']  
let upper_case = ['A'-'Z']  
let letter = upper_case | lower_case  
let letters = letter +
```

10/26/23

40

Example : test.mll

```
rule main = parse  
  (digits)'.digits as f { Float (float_of_string f) }  
  | digits as n          { Int (int_of_string n) }  
  | letters as s         { String s }  
  | _ { main lexbuf }  
{ let newlexbuf = (Lexing.from_channel stdin) in  
  print_newline ();  
  main newlexbuf }
```

10/26/23

41

Example

```
# #use "test.mll";  
...  
val main : Lexing.lexbuf -> result = <fun>  
val __ocaml_lex_main_rec : Lexing.lexbuf -> int ->  
  result = <fun>  
hi there 234 5.2  
- : result = String "hi"
```

What happened to the rest!?

10/26/23

42

Example

```
# let b = Lexing.from_channel stdin;;
# main b;;
hi 673 there
- : result = String "hi"
# main b;;
- : result = Int 673
# main b;;
- : result = String "there"
```

10/26/23

43

Your Turn

- Work on MP8
 - Add a few keywords
 - Implement booleans and unit
 - Implement Ints and Floats
 - Implement identifiers

10/26/23

44

Problem

- How to get lexer to look at more than the first token at one time?
- Answer: *action* has to tell it to -- recursive calls
 - Not what you want to sew this together with `ocamlyacc`
- Side Benefit: can add “state” into lexing
- Note: already used this with the `_` case

10/26/23

45

Example

```
rule main = parse
  (digits) '.' digits as f { Float (float_of_string f) :: main lexbuf }
  | digits as n           { Int (int_of_string n) :: main lexbuf }
  | letters as s         { String s :: main lexbuf }
  | eof                  { [] }
  | _                    { main lexbuf }
```

10/26/23

46

Example Results

```
hi there 234 5.2
- : result list = [String "hi"; String "there"; Int 234; Float 5.2]
#
```

Used Ctrl-d to send the end-of-file signal

10/26/23

47

Dealing with comments

First Attempt

```
let open_comment = "("
let close_comment = "*"
rule main = parse
  (digits) '.' digits as f { Float (float_of_string f) :: main lexbuf }
  | digits as n           { Int (int_of_string n) :: main lexbuf }
  | letters as s         { String s :: main lexbuf }
```

10/26/23

48

Dealing with comments

```
| open_comment { comment lexbuf }
| eof          { [] }
| _ { main lexbuf }
and comment = parse
  close_comment { main lexbuf }
| _            { comment lexbuf }
```

10/26/23

49

Dealing with nested comments

```
rule main = parse ...
| open_comment { comment 1 lexbuf }
| eof          { [] }
| _ { main lexbuf }
and comment depth = parse
  open_comment { comment (depth+1) lexbuf }
| close_comment { if depth = 1
                  then main lexbuf
                  else comment (depth - 1) lexbuf }
| _            { comment depth lexbuf }
```

10/26/23

50

Dealing with nested comments

```
rule main = parse
  (digits) '!' digits as f { Float (float_of_string f) ::
    main lexbuf }
| digits as n { Int (int_of_string n) :: main
  lexbuf }
| letters as s { String s :: main lexbuf }
| open_comment { (comment 1 lexbuf) }
| eof          { [] }
| _ { main lexbuf }
```

10/26/23

51

Dealing with nested comments

```
and comment depth = parse
  open_comment { comment (depth+1) lexbuf }
| close_comment { if depth = 1
                  then main lexbuf
                  else comment (depth - 1) lexbuf }
| _            { comment depth lexbuf }
```

10/26/23

52

Types of Formal Language Descriptions

- Regular expressions, regular grammars
- Context-free grammars, BNF grammars, syntax diagrams

- Finite state automata
- Pushdown automata
- Whole family more of grammars and automata – covered in automata theory

10/26/23

53

Sample Grammar

- Language: Parenthesized sums of 0's and 1's
- $\langle \text{Sum} \rangle ::= 0$
- $\langle \text{Sum} \rangle ::= 1$
- $\langle \text{Sum} \rangle ::= \langle \text{Sum} \rangle + \langle \text{Sum} \rangle$
- $\langle \text{Sum} \rangle ::= (\langle \text{Sum} \rangle)$

10/26/23

54

BNF Grammars

- Start with a set of characters, **a,b,c,...**
 - We call these *terminals*
- Add a set of different characters, **X,Y,Z,...**
 - We call these *nonterminals*
- One special nonterminal **S** called *start symbol*

10/26/23

55

BNF Grammars

- BNF rules (aka *productions*) have form
$$\mathbf{X} ::= y$$
where **X** is any nonterminal and *y* is a string of terminals and nonterminals
- BNF *grammar* is a set of BNF rules such that every nonterminal appears on the left of some rule

10/26/23

56

Sample Grammar

- Terminals: 0 1 + ()
- Nonterminals: <Sum>
- Start symbol = <Sum>
- <Sum> ::= 0
- <Sum> ::= 1
- <Sum> ::= <Sum> + <Sum>
- <Sum> ::= (<Sum>)
- Can be abbreviated as
$$\langle \text{Sum} \rangle ::= 0 \mid 1 \mid \langle \text{Sum} \rangle + \langle \text{Sum} \rangle \mid (\langle \text{Sum} \rangle)$$

10/26/23

57

BNF Derivations

- Given rules
$$\mathbf{X} ::= y\mathbf{Z}w \text{ and } \mathbf{Z} ::= v$$
we may replace **Z** by *v* to say
$$\mathbf{X} \Rightarrow y\mathbf{Z}w \Rightarrow yvw$$
- Sequence of such replacements called *derivation*
- Derivation called *right-most* if always replace the right-most non-terminal

10/26/23

58

BNF Derivations

- Start with the start symbol:

<Sum> =>

10/26/23

59

BNF Derivations

- Pick a non-terminal

<Sum> =>

10/26/23

60

BNF Derivations

- Pick a rule and substitute:
 - $\langle \text{Sum} \rangle ::= \langle \text{Sum} \rangle + \langle \text{Sum} \rangle$
- $$\langle \text{Sum} \rangle \Rightarrow \langle \text{Sum} \rangle + \langle \text{Sum} \rangle$$

10/26/23

61

BNF Derivations

- Pick a non-terminal:
- $$\langle \text{Sum} \rangle \Rightarrow \langle \text{Sum} \rangle + \langle \text{Sum} \rangle$$

10/26/23

62

BNF Derivations

- Pick a rule and substitute:
 - $\langle \text{Sum} \rangle ::= (\langle \text{Sum} \rangle)$
- $$\langle \text{Sum} \rangle \Rightarrow \langle \text{Sum} \rangle + \langle \text{Sum} \rangle$$
- $$\Rightarrow (\langle \text{Sum} \rangle) + \langle \text{Sum} \rangle$$

10/26/23

63

BNF Derivations

- Pick a non-terminal:
- $$\langle \text{Sum} \rangle \Rightarrow \langle \text{Sum} \rangle + \langle \text{Sum} \rangle$$
- $$\Rightarrow (\langle \text{Sum} \rangle) + \langle \text{Sum} \rangle$$

10/26/23

64

BNF Derivations

- Pick a rule and substitute:
 - $\langle \text{Sum} \rangle ::= \langle \text{Sum} \rangle + \langle \text{Sum} \rangle$
- $$\langle \text{Sum} \rangle \Rightarrow \langle \text{Sum} \rangle + \langle \text{Sum} \rangle$$
- $$\Rightarrow (\langle \text{Sum} \rangle) + \langle \text{Sum} \rangle$$
- $$\Rightarrow (\langle \text{Sum} \rangle + \langle \text{Sum} \rangle) + \langle \text{Sum} \rangle$$

10/26/23

65

BNF Derivations

- Pick a non-terminal:
- $$\langle \text{Sum} \rangle \Rightarrow \langle \text{Sum} \rangle + \langle \text{Sum} \rangle$$
- $$\Rightarrow (\langle \text{Sum} \rangle) + \langle \text{Sum} \rangle$$
- $$\Rightarrow (\langle \text{Sum} \rangle + \langle \text{Sum} \rangle) + \langle \text{Sum} \rangle$$

10/26/23

66



BNF Derivations

- Pick a non-terminal:

$$\begin{aligned} \langle \text{Sum} \rangle &\Rightarrow \langle \text{Sum} \rangle + \langle \text{Sum} \rangle \\ &\Rightarrow (\langle \text{Sum} \rangle) + \langle \text{Sum} \rangle \\ &\Rightarrow (\langle \text{Sum} \rangle + \langle \text{Sum} \rangle) + \langle \text{Sum} \rangle \\ &\Rightarrow (\langle \text{Sum} \rangle + 1) + \langle \text{Sum} \rangle \end{aligned}$$