

Computer Science 425

Distributed Systems

CS 425 / CSE 424 / ECE 428

Fall 2012

Indranil Gupta (Indy)

Sep 4, 2012

Lecture 3

Cloud Computing - 2

Recap

- **Last Thursday's Lecture**

- **Clouds vs. Clusters**
 - » **At least 3 differences**
- **A Cloudy History of Time**
 - » **Clouds are the latest in a long generation of distributed systems**

- **Today's Lecture**

- **Cloud Programming: MapReduce (the heart of Hadoop)**
- **Grids**

Programming Cloud Applications - New Parallel Programming Paradigms: **MapReduce**

- **Highly-Parallel Data-Processing**
- **Originally designed by Google (OSDI 2004 paper)**
- **Open-source version called **Hadoop**, by Yahoo!**
 - Hadoop written in Java. Your implementation could be in Java, or any executable
- **Google (MapReduce)**
 - Indexing: a chain of **24 MapReduce jobs**
 - ~200K jobs processing **50PB**/month (in 2006)
- **Yahoo! (Hadoop + Pig)**
 - WebMap: a chain of **100 MapReduce jobs**
 - **280 TB** of data, 2500 nodes, 73 hours
- **Annual Hadoop Summit: 2008 had 300 attendees, now close to 1000 attendees**


What is MapReduce?

- Terms are borrowed from Functional Language (e.g., Lisp)

Sum of squares:


- **(map square '(1 2 3 4))**
 - Output: (1 4 9 16)
 - [processes each record sequentially and independently]
- **(reduce + '(1 4 9 16))**
 - (+ 16 (+ 9 (+ 4 1)))
 - Output: 30
 - [processes set of all records in groups]
- Let's consider a sample application: **Wordcount**
 - You are given a huge dataset (e.g., collection of webpages) and asked to list the count for each word appearing in the dataset

Map



- **Process individual records to generate intermediate key/value pairs.**


Welcome Everyone
Hello Everyone



Input <filename, file text>


Key	Value
Welcome	1
Everyone	1
Hello	1
Everyone	1

Map




- **Parallelly** Process individual records to generate intermediate key/value pairs.


MAP TASK 1



Map



- **Parallely** Process **a large number of** individual records to generate intermediate key/value pairs.




Reduce



- Processes and merges all intermediate values associated per key (that's the group)

Welcome 1
Everyone 1
Hello 1
Everyone 1




Key ↓	Value ↓
Everyone	2
Hello	1
Welcome	1

Reduce



- **Parallelly** Processes and merges all intermediate values **by partitioning keys**



Hadoop Code - Map

```
public static class MapClass extends MapReduceBase
    implements Mapper<LongWritable, Text, Text,
        IntWritable> {

    private final static IntWritable one =
        new IntWritable(1);
    private Text word = new Text();

    public void map( LongWritable key, Text value,
        OutputCollector<Text, IntWritable> output,
        Reporter reporter)
        throws IOException {
        String line = value.toString();
        StringTokenizer itr = new StringTokenizer(line);
        while (itr.hasMoreTokens()) {
            word.set(itr.nextToken());
            output.collect(word, one);
        }
    }

}

// Source: http://developer.yahoo.com/hadoop/tutorial/module4.html#wordcount
```

Hadoop Code - Reduce

```
public static class ReduceClass extends MapReduceBase
    implements Reducer<Text, IntWritable, Text,
        IntWritable> {
    public void reduce(
        Text key,
        Iterator<IntWritable> values,
        OutputCollector<Text, IntWritable> output,
        Reporter reporter)
        throws IOException {
        int sum = 0;
        while (values.hasNext()) {
            sum += values.next().get();
        }
        output.collect(key, new IntWritable(sum));
    }
}
```

Hadoop Code - Driver

```
// Tells Hadoop how to run your Map-Reduce job
public void run (String inputPath, String outputPath)
    throws Exception {
    // The job. WordCount contains MapClass and Reduce.
    JobConf conf = new JobConf(WordCount.class);
    conf.setJobName("mywordcount");
    // The keys are words
    (strings) conf.setOutputKeyClass(Text.class);
    // The values are counts (ints)
    conf.setOutputValueClass(IntWritable.class);
    conf.setMapperClass(MapClass.class);
    conf.setReducerClass(ReduceClass.class);
    FileInputFormat.addInputPath(
        conf, new Path(inputPath));
    FileOutputFormat.setOutputPath(
        conf, new Path(outputPath));
    JobClient.runJob(conf);
}
```

Some Other Applications of MapReduce

Distributed Grep:

- Input: large set of files
- Output: lines that match pattern
- Map – *Emits a line if it matches the supplied pattern*
- Reduce - *Copies the intermediate data to output*

Some Other Applications of MapReduce (2)

Reverse Web-Link Graph

- Input: Web graph: tuples (a, b) where (page a → page b)
- Output: For each page, list of pages that link to it
- Map – *process web log and outputs <target, source>*
- Reduce - *emits <target, list(source)>*

Some Other Applications of MapReduce (3)

Count of URL access frequency

- Input: Log of accessed URLs from proxy server
- Output: For each URL, % of total accesses for that URL
- Map – *Process web log and outputs <URL, 1>*
- Multiple Reducers - *Emits <URL, URL_count>*
(So far, like Wordcount. But still need %)
- Chain another MapReduce job after above one
- Map – *Processes <URL, URL_count> and outputs <1, (<URL, URL_count>)>*
- 1 Reducer – Sums up *URL_count's* to calculate overall_count.
Emits <URL, URL_count/overall_count>

Some Other Applications of MapReduce (4)

**Map task's output is sorted (e.g., quicksort)
Reduce task's input is sorted (e.g., mergesort)**

Sort

- **Input: Series of (key, value) pairs**
- **Output: Sorted <value>s**
- **Map – *<key, value> -> <value, _> (identity)***
- **Reducer – *<key, value> -> <key, value> (identity)***
- **Partitioning function – partition keys across reducers based on ranges**
 - » **Take data distribution into account to balance reducer tasks**

Programming MapReduce

- **Externally: For user**
 1. Write a Map program (short), write a Reduce program (short)
 2. Decide number of tasks and submit job; wait for result
 3. Need to know nothing about parallel/distributed programming!
- **Internally: For the cloud (and for us distributed systems researchers)**
 1. Parallelize Map
 2. Transfer data from Map to Reduce
 3. Parallelize Reduce
 4. Implement Storage for Map input, Map output, Reduce input, and Reduce output

Inside MapReduce



X-Ray

- For the cloud (and for us distributed systems researchers)
 1. Parallelize Map: **easy!** **Shard** the data equally into requested map tasks.
 2. Transfer data from Map to Reduce:
 - » All Map output tuples with same key assigned to same Reduce task
 - » use **partitioning function**: example is to hash the key of the tuple, modulo number of reduce jobs, or identity function for sort
 3. Parallelize Reduce: **easy!** Assign keys uniformly across requested reduce tasks. Reduce task knows its assigned keys (through master).
 4. Implement Storage for Map input, Map output, Reduce input, and Reduce output
 - » Map input: from **distributed file system**
 - » Map output: to local disk (at Map node); uses **local file system**
 - » Reduce input: from (multiple) remote disks; uses local file systems
 - » Reduce output: to distributed file system

local file system = Linux FS, etc.

distributed file system = GFS (Google File System), HDFS (Hadoop Distributed File System)

Internal Workings of MapReduce - Example




Figure 1: Execution overview

- **Failures**

- Master tracks **progress** of each task
- reschedules task with stopped progress or on failed machine
- Highly simplified explanation here – failure-handling is more sophisticated (next lecture!)

- **Slow tasks**


- The slowest machine slows the entire job down
- Hadoop **Speculative Execution**: Spawn multiple copies of tasks that have a slow progress. When one finishes, stop other copies.

- **What about bottlenecks within the datacenter?**


- CPUs? Disks? Switches?

*Testbed: 1800 servers each with 4GB RAM, dual 2GHz Xeon,
dual 169 GB IDE disk, 100 Gbps, Gigabit ethernet per machine*

Grep



*Workload: 10^{10} 100-byte records to extract records
matching a rare pattern (92K matching records)*




Clouds are data-intensive
Grids are/were computation-intensive

What is a Grid?

Example: Rapid Atmospheric Modeling System, ColoState U



- **Hurricane Georges, 17 days in Sept 1998**
 - “RAMS modeled the mesoscale convective complex that dropped so much rain, in good agreement with recorded data”
 - Used 5 km spacing instead of the usual 10 km
 - Ran on 256+ processors
- **Computation-intensive application rather than data-intensive**
- ***Can one run such a program without access to a supercomputer?***

Wisconsin




***Distributed
Computing
Resources***


MIT




NCSA





An Application Coded by a Physicist



An Application Coded by a Physicist





Wisconsin







Allocation? **Scheduling?**


MIT




NCSA










Internal Allocation & Scheduling
Monitoring
Distribution and Publishing of Files

The Grid Recently



Some are 40Gbps links!
(The TeraGrid links)



"A parallel Internet"

Question to Ponder

- **Cloud computing vs. Grid computing: what are the differences?**



MP1, HW1

- **MP1, HW1 out today**
 - MP1 due 9/16 (Sun midnight)
 - HW1 due 9/20 (in class)
 - For HW: Individual. You are allowed to discuss the *problem* and *concepts* (e.g., in study groups), but you cannot discuss the *solution*.
 - For MP: Groups of 2 students (pair up with someone taking class for same # credits)
 - » If you don't have a partner, hang around after class today
 - » Please report groups to us **by this Thursday 9/16**. Subject line: "425 MP group"
 - Please read instructions carefully!
 - Start NOW

MP1: Logging + Testing

- **Distributed Systems hard to debug (you'll know soon!)**
- **Creating log files at each machine to tabulate important messages/errors/status is critical to debugging**
- **MP1: Write a distributed program that lets you grep (+ regexp's) all the log files across a set of machines (from any of those machines)**
- **How do you know your program works?**
 - Write **unit tests**
 - E.g., Generate non-identical logs at each machine, then run grep from one of them and automatically verify that you receive the answer you expect
 - Writing tests can be hard work, but it is industry standard
 - We encourage (but don't require) that you write tests for MP2 onwards

Readings

- **For next lecture**
 - **Failure Detection**
 - **Readings: Section 15.1, parts of Section 2.4.2**