

UNIVERSITY OF ILLINOIS AT URBANA-CHAMPAIGN  
Department of Electrical and Computer Engineering

ECE 498MH PRINCIPLES OF SIGNAL ANALYSIS  
Fall 2014

**MIDTERM EXAM 2**

Friday, NOVEMBER 7, 2014

- This is a **CLOSED BOOK** exam. You are allowed one page, front and back, of hand-written notes.
- There are a total of 100 points in the exam. Each problem specifies its point total. Plan your work accordingly.
- You must **SHOW YOUR WORK** to get full credit.

Problem	Score
1	
2	
3	
4	
Total	

Name: \_\_\_\_\_

**Problem 1 (25 points)**

Consider the system

$$y[n] = \begin{cases} x[n] & n \text{ even} \\ 0 & n \text{ odd} \end{cases}$$

- (a) Is this system linear? Prove your answer.

NAME: \_\_\_\_\_

Exam 2

Page 3

(b) Is this system time-invariant? Prove your answer.

NAME: \_\_\_\_\_

Exam 2

Page 4

**Problem 2 (25 points)**

A particular LTI system has the impulse response

$$h[n] = \delta[n] + \delta[n - 2]$$

- (a) What is the frequency response,  $H(\omega)$ , of this system?

NAME: \_\_\_\_\_

Exam 2

Page 5

(b) Suppose the input is  $x[n] = \delta[n] + \delta[n - 3]$ . What is the output?

**Problem 3 (25 points)**

Suppose you have a signal sampled at  $F_s = 600$  samples/second. You wish to create a notch filter to eliminate a noise component at 60Hz. You choose to do this using the following filter:

$$H(z) = \frac{(1 - r_1 z^{-1})(1 - r_2 z^{-1})}{(1 - p_1 z^{-1})(1 - p_2 z^{-1})}$$

- (a) Specify the values of the poles  $p_1, p_2$  and the zeros  $r_1, r_2$ . Note that there is one free parameter in your answer that is not specified by the problem statement; you may set that free parameter to any reasonable value.

(b) Now suppose you are given a system function

$$H(z) = \frac{(1 - r_1 z^{-1})(1 - r_2 z^{-1})}{(1 - p_1 z^{-1})(1 - p_2 z^{-1})}$$

and you wish to implement this using the equation

$$y[n] = x[n] + b_1 x[n - 1] + b_2 x[n - 2] - a_1 y[n - 1] - a_2 y[n - 2]$$

Find  $b_1$ ,  $b_2$ ,  $a_1$  and  $a_2$  in terms of  $r_1$ ,  $r_2$ ,  $p_1$  and  $p_2$ .

**Problem 4 (25 points)**

Suppose you want to design a band-stop filter as follows:

$$D(\omega) = \begin{cases} 1 & |\omega| < \frac{\pi}{5} \\ 0 & \frac{\pi}{5} < |\omega| < \frac{\pi}{2} \\ 1 & \text{otherwise} \end{cases}$$

- (a) Find the desired impulse response,  $d[n]$ .



- (b) Suppose you are willing to tolerate transition bands of up to  $\Delta\omega = \frac{\pi}{32}$  radians/sample (measured from passband ripple to stopband ripple), but that you want the ripples to be as small as possible. What type of window should you use, and how long should it be?