

# ECE 445


# Final Presentation

# Team 48


Phoebe Chen, Mary Rose Farruggio, Owen Thamban

Professor: Dr. Olga Mironenko

TA: Abhisheka Mathur Sekar



# Introduction



# Team 48

## Electrochromic Bird-Friendly Windows


Phoebe Chen  
Computer Engineer



Mary Rose Farruggio  
Electrical Engineer



Owen Thamban  
Electrical Engineer




# Problem

- Approximately one billion fatal bird-window collision in America each year
- Current solutions significantly compromise visibility/aesthetic appeal
  - Adoption is low
- Conservation concern




# Problem




# Objective

To lower the rate of fatal bird-window collisions in an efficient manner while keeping the aesthetic appeal of the window




# Solution Design



# Initial Idea

- Need to make birds aware of the hazard  
-> Make window visible ->  
Electrochromic  
Materials
- Detect Birds  
approaching and  
change opacity






# Initial Idea

- Use ultrasonic sensors to detect birds approaching
- Change opacity of electrochromic panels when a bird is detected

**Side View**




**Front View**






**Key**

■ Ultrasonic Sensor  
▲ area of ultrasonic detection




# Design Revision

- Fast flight speed and slow reaction time -> adjusted dimensions
- Aesthetically unappealing -> use hollow frame
- Can't distinguish between birds and rain, leaves, etc. -> add image processing




# Design Revision


- Insufficient number of pins on microcontroller  
->decrease sensors to minimum number necessary
- Limited field of vision->move thermal camera to frame's center



# Image Processing




This heatmap visualization displays the 2016 US Presidential election results by county. The map uses a color scale where light green represents Clinton and dark blue represents Trump. The visualization shows a clear geographic divide, with Clinton winning the majority of counties in the Northeast, Midwest, and West Coast, while Trump won the majority of counties in the South and Great Plains regions.



- POWER SUBSYSTEM
- CONTROLS SUBSYSTEM
- OBJECT CLASSIFICATION SUBSYSTEM
- OBJECT DETECTION SUBSYSTEM
- BIRD INTERFACE



# High Level Requirements



The header features a light blue background with several small, dark blue bird silhouettes in flight. On the right side, there is a large, stylized graphic composed of a grid of squares in various shades of blue and green, arranged in a pattern that resembles a bird's wing or a flock of birds in flight.

# High Level Requirements

When the system is at rest the panels must be kept in their transparent state. The system is considered at rest before a bird is detected or after a bird has exited.



The header features a light blue background with several small, dark blue bird silhouettes in flight. On the right side, there is a decorative graphic consisting of a grid of squares in various shades of blue and green, arranged in a pattern that tapers towards the left.


# High Level Requirements

The system must be able to successfully detect an object traveling at  $7.6 \text{ m/s}$  or less of length  $\geq 11 \text{ cm}$  and width  $\geq 19 \text{ cm}$  (minimum length and wingspan of the seven birds with the highest rates of window collisions) entering or exiting through the front of the  $24 \times 24 \times 58 \text{ cm}$  rectangular prism encompassed by the frame in  $\geq 80\%$  of trials.



# High Level Requirements

When the system determines that an object has been detected entering the frame-encompassed area, it must successfully transition one or more of the electrochromic panels from transparent to opaque.




The background of the slide features a light blue sky with several small, dark blue bird silhouettes in flight, scattered across the upper left and center. On the right side, there is a large, stylized graphic of a bird's head and neck, composed of a grid of small squares in various shades of blue and green, creating a pixelated or mosaic effect.

# Assumptions


- Majority head-on collisions
- One bird at a time
- Semi-species specific
  - White-throated Sparrow
  - Ovenbird
  - Common Yellowthroat
  - Dark-eyed Junco
  - Brown Creeper
  - Hermit Thrush
  - Black-and-white Warbler

# Successes & Challenges



# Challenges

- Physical design compromise
- High current draw from panels
- Ultrasonic sensor accuracy
- Microcontroller malfunction/switch to Arduino (less pins)
- Improvised digital switches
- Arduino limited current draw
- Not enough parts
- Integration




The background of the slide features a light blue sky with several small, dark blue birds in flight. On the right side, there is a large, stylized graphic composed of a grid of squares in various shades of blue and green, creating a pixelated or mosaic effect.


# Successes

- Sturdy, portable, clean-cut frame
- Included DC/AC converters (altered parameters)
- Fast Ultrasonic Sensor/Microcontroller Response Time (7.85 m/s)
- Consistent detection under 58 cm ( $\geq 80\%$  of trials)
- Full and location-specific panel transitions
- Accurate image processing/object tracking
- No panel damage


# Results



# Interface





DC/AC Converter Input and Output





# Detection/Interface





# Performance: Ultrasonic Sensors

Ultrasonic Sensor 3		Ultrasonic Sensor 4		Ultrasonic Sensor 5	
Ruler-Measured	Sensor-Measured Distance	Ruler-Measured	Sensor-Measured Distance	Ruler-Measured	Sensor-Measured Distance
5	4.8	5	5.44	5	4.27
10	10.41	10	11.78	10	9.23
15	15.8	15	15.64	15	15.62
20	20.94	20	19.47	20	21.68
25	25.04	25	25.67	25	25.14
30	29.36	30	31.52	30	30.08
35	36.62	35	35.57	35	36.2
40	39.03	40	42.19	40	38.95
45	44.09	45	42.19	45	40.46
50	48.32	50	49.48	50	48.21
55	49.63	55	49.55	55	49.48
60	50.01	60	56.08	60	X
65	50.11	65	42.21	65	
70	X	70	X	70	
75		75		75	
80		80		80	

Ultrasonic Sensor  
Accuracy (cm)

# Results: Classification




# Conclusions & Takeaways

- Order many, many spare parts as early as possible
- Datasheet accuracy varies
- Make accountability a habit early on
- Unit test in short bursts
- Has potential for larger applications




# Recommendations


- Economies of scale-> increase application size
- Testing with live birds
- Waterproof system for field applications
- Adapt parameters based on geographical location (temperature, threshold)
- Implement more efficient image processing algorithm
- Median Filter



Questions?



# Appendix



# Block requirements: Control Subsystem

- The control subsystem must be able to calculate distances correctly based on input from the ultrasonic sensors. For measured distances below 20 cm, the accuracy of the calculated distances should be within 5 cm. For measured distances between 20-100 cm, the accuracy of the calculated distances should be within 10 cm.
- The control subsystem must be able to signal to the electrochromic panels to change opacity once an object is detected. I/O pins controlling the opacity should transition to a high voltage (2.7-5.5 V) in 95% of trials.
- The control system must be able to initiate image processing in the Raspberry Pi. The interrupt pin of the microcontroller feeding into the Raspberry Pi must go high (2.7-5.5 V) when an object is detected in 95% of trials.



# Block requirements, Object Detection and Object Classification Subsystem

## Object Detection

- For measured distances below 20 cm, the accuracy of the calculated distances should be within 5 cm in  $\geq 95\%$  of trials. For measured distances between 20-100 cm, the accuracy of the calculated distances should be within 10 cm in  $\geq 95\%$  of trials.
- The ultrasonic sensors must be mounted on the frame in such a way that they can accurately determine which electrochromic panel zones the detected objects are entering/exiting within the 3D frame area in  $\geq 95\%$  of trials.

## Object Classification

- The image processing can correctly identify warm blooded objects within the 58 cm x 58 cm x 92 cm frame space in  $\geq 85\%$  of trials.

# Block requirements: Bird Interface and Power subsystems

## Bird Interface

- The opacity must visibly transition between transparent and opaque in response to the microcontroller.

## Power subsystem

- The opacity must visibly transition between transparent and opaque in response to the microcontroller.
- The voltage regulator must supply a DC input voltage 2.5-3.5V to the DC to AC converters feeding into the electrochromic panels at all times the system is operating.

