# Autonomous Vehicle with Sign Recognition and Obstacle Clearing through Wi-Fi

By

Pai Zhang (paiz4) Rui Zhang (rui14) Wendi Wang (wendiw2) Pengyu Zhu (pengyuz4)

Sponsored By Prof. Howard Yang

TA:

Ruihao Du

Project No.19 Project Proposal for ECE 445, Spring 2025 March 13<sup>th</sup>, 2025

1

# **Table of Contents**

Project Proposal				
1	Intro	oduction	4	
	1.1	Problem	4	
	1.2	Solution and Visual Aid	5	
	1.3	High-level Requirements	7	
2	Des	sign and Requirements	8	
	2.1	Image Capture and Simple Analysis Subsystem	8	
		2.1.1 Subsystem Overview	8	
		2.1.2 Acceptance Requirements	8	
		2.1.3 Difficulty and Risk Analysis	10	
		2.1.4 Tolerance Analysis	10	
	2.2	Microcontroller Subsystem	10	
		2.2.1 Subsystem Overview	10	
		2.2.2 Acceptance Requirements	10	
		2.2.3 Difficulty and Risk Analysis	11	
		2.2.4 Tolerance Analysis	11	
	2.3	Thorough Image Analysis Subsystem	11	
		2.3.1 Subsystem Overview	11	
		2.3.2 Acceptance Requirements	11	
		2.3.3 Difficulty and Risk Analysis	12	
		2.3.4 Tolerance Analysis	12	
	2.4	Microcontroller Subsystem	12	
		2.4.1 Subsystem Overview	12	
		2.4.2 Acceptance Requirements	12	
		2.4.3 Difficulty and Risk Analysis	13	
		2.4.4 Tolerance Analysis	13	
	2.5	Output Subsystem	13	

	2.5.1 Subsystem Overview	. 13		
	2.5.2 Acceptance Requirements	. 13		
	2.5.3 Difficulty and Risk Analysis	. 13		
	2.5.4 Tolerance Analysis	. 14		
2		15		
3	Etnics and Safety	15		
	3.1 Ethical Issues	. 15		
	3.2 Safety Issues	. 15		
Re	References			

## **Project Proposal**

## **1** Introduction

Autonomous vehicles have become popular in industrial research and daily life for a long time, with advanced functions like reading signal lights and giving ways to pedestrians. In recent years, many efforts have been devoted to introducing autonomous vehicles to urban traffic and domestic life. However, among those universalized autonomous vehicles like Tesla and Cruise, they are seldom brought to campus as shuttle buses or trash carts due to high costs. It would bring much convenience to students' campus life if some low-cost and efficient autonomous vehicles help students commute and provide some safety guarantees in obstacle detection and self-speed control by reading speed limit signs. We aim to develop the core of such low-cost autonomous vehicles to potentially take the responsibilities of commuting and obstacle-clearing, enabling wireless transmission to provide efficiency via campus Wi-Fi.

#### 1.1 Problem

Based on our personal life experience and class schedules on campus, we observe that most undergraduate students have a tight class schedule, resulting in insufficient time to transfer from one classroom to another between consecutive classes. Some choose to ride a bicycle for commuting. However, the number of bicycles around each teaching building is often limited and unevenly distributed. Classrooms with a large student current might be matched to an area with only a few available bicycles. Consequently, manually moving and re-distributing those bicycles to support student commuting needs places an additional burden on campus staff. In the meanwhile, we also notice that the ratio of cleaning staff and the campus area is quite low. The campus is too vast compared to the number of personnel responsible for cleaning, laying down a heavy workload to clean trash and obstacles on the campus, especially in the leaf-falling season or rainy and snowy weather.

According to two observations mentioned above, we came up with the idea of incorporating autonomous driving systems into our campus life and study as shuttle buses or trash carts. However, the most popular autonomous driving vehicles in the market are expensive and suitable for more complex situations other than campus life. Therefore, considering the special properties

4

of the campus (everywhere Wi-Fi coverage and relatively simple road conditions), we aim for a low-cost autonomous vehicle designed and constructed using basic mechanical and electronic components like Arduino board, Wi-Fi modules, robot arms, etc.

#### **1.2** Solution and Visual Aid

Specifically, our solution of an autonomous vehicle supporting speed limit sign recognition and obstacle-clearing elaborates as follows. Considering that the speed limit on campus is usually 30 km/h and a safe distance of 2 meters, the camera contained in the Raspberry Pi captures an image every other 0.24 seconds (i.e. at a frequency of 4.167 Hz). Another specific factor on the campus is Wi-Fi signals and availability. Each time the camera snaps a shot, we consider two following cases:

- When Wi-Fi is available, the captured image is sent to the remote server for thorough powerful image analysis and obstacle/speed limit sign recognition. After the remote server returns the corresponding obstacle type or the speed in km/h, such information is sent to the microcontroller (Arduino Uno R3) via Wi-Fi again. On receiving obstacle or speed information, Arduino Uno R3 transmits it to the vehicle motors or the robot arm for self-speed adjustments or obstacle clearing via UART protocols and Wi-Fi modules respectively. For visual aid of this situation, please refer to Figure 1a and Figure 1b.
- When Wi-Fi is unavailable, the Raspberry Pi takes the responsibility to analyze the image using simpler computer vision algorithms like CNN [1] compared to the remote server due to limited GPU capability. After the Raspberry Pi returns the corresponding speed in km/h, such information is sent to the microcontroller (Arduino Uno R3) via UART protocols. On receiving speed information, Arduino Uno R3 transmits it to the vehicle motors for self-speed adjustments via UART protocols again.

Compared to existing autonomous vehicles, our solution is low-cost and efficient since it is constructed with basic and traditional electronic devices. It also combines the efficiency and convenience of Wi-Fi signals covered on the campus to enable almost simultaneous information transmission. In conclusion, the potential benefits and contributions of this project are as follows:



(c) A visual aid of our solution on speed limit sign recognition when Wi-Fi is not available.

Figure 1: A visual aid of our proposed solution.

- Provides a low-cost and efficient autonomous vehicle via Wi-Fi for campus usage.
- The core of such autonomous vehicles can be extended to autonomous campus shuttle buses to satisfy the needs of commuting among students.
- Such autonomous vehicles can also facilitate trash clearing and obstacle-detecting tasks on the campus to promote its comfort and beauty.

## 1.3 High-level Requirements

Here are four quantitative high-level requirements for our proposed solution, aiming to solve students' commuting issues and the heavy workload of trash clearing on the campus:

- The vehicle must navigate autonomously with the aid of speed limit signs only on the campus, for at least 30 minutes.
- Total time of each image capturing, image analysis, and information transmission must be less than 0.24 seconds, the time interval between two shots of the Raspberry Pi camera.
- The robot arm must clear an obstacle within 0.24 seconds, which is the time interval between two shots of the Raspberry Pi camera.
- The accuracy of recognizing speed limit signs and obstacles must be above 80%.

## **2** Design and Requirements

Our design is based on Arduino Uno R3 (as the microcontroller), with the aid of the Raspberry Pi 4B as the camera and simple image analyzer, the Wi-Fi module ESP8266 as the information transmission media, a 4-axis 4-degree robot arm as the obstacle-clearing tool, and a vehicle with two DC motors carrying all components as an autonomous driving system. The detailed workflow and block diagram of our design can be found in Figure 2.

#### 2.1 Image Capture and Simple Analysis Subsystem

#### 2.1.1 Subsystem Overview

The main component in the *Image Capture and Simple Analysis Subsystem* is the Raspberry Pi 4B. With a camera of high resolutions and wide angles, it captures images of the speed limit signs and obstacles every 0.24 seconds to ensure safety and promptness. When Wi-Fi signals are unavailable, it can also take the responsibility of simple image analysis to ensure the self-speed adjustment of the autonomous vehicle. This subsystem is closely related to the *Microcontroller Subsystem* as the Raspberry Pi 4B communicates with the microcontroller Arduino Uno R3 via UART for image and speed information transmissions.

#### 2.1.2 Acceptance Requirements

- Requirement 1: The accuracy of speed limit sign recognition must be larger than 80%.
- *Verification 1*: Generate images of different speed limits ranging from 0 to 30 km/h (according to the rules on the campus) to test the recognition algorithm on the Raspberry Pi 4B and record the accuracy of recognition.
- *Requirement 2*: The time of speed limit sign recognition must be less than 0.08 seconds, one-third of the time interval between two shots of the Raspberry Pi camera.
- *Verification 2*: Generate images of different speed limits ranging from 0 to 30 km/h (according to the rules on the campus) to test the recognition algorithm on the Raspberry Pi 4B and record the average recognition time.



(a) Workflow of our proposed solution.



(b) Block diagram of our proposed solution consisting of four subsystems and a power supply module.

Figure 2: Block Diagrams in Hardware and Software Design.

#### 2.1.3 Difficulty and Risk Analysis

Since the GPU capability and storage space of the Raspberry Pi 4B is limited, finding and finetuning a CNN-based algorithm to detect obstacles and speed limit signs while satisfying the accuracy requirement of 80% might take some time of careful consideration.

#### 2.1.4 Tolerance Analysis

We use accuracy and time to evaluate the performance of this subsystem. If the time of speed limit sign recognition is less than 0.08 seconds and the accuracy of speed limit sign recognition is larger than 80%, we consider this subsystem to be successfully constructed and functioning.

#### 2.2 Microcontroller Subsystem

#### 2.2.1 Subsystem Overview

The main component in the *Microcontroller Subsystem* is the Arduino UNO R3. With a power supply of 5 volts direct current, it connects the components of the Raspberry Pi 4B, the remote cloud server, the robot arm, and the vehicle across all other subsystems. It enables simultaneous reading and writing via UART to receive information from the Raspberry Pi 4B in the *Image Capture and Simple Analysis Subsystem* and delivers it to the vehicle to adjust motor speed via PWM. It also enables Wi-Fi transmission with the remote cloud server in the *Thorough Image Analysis Subsystem* by controlling the Wi-Fi module.

#### 2.2.2 Acceptance Requirements

- *Requirement 1*: The time of UART transmission must be less than 0.08 seconds, one-third of the time interval between two shots of the Raspberry Pi camera.
- *Verification 1*: Record the average UART transmission time by recording the time when the Raspberry Pi 4B generates the result and the time Arduino receives.
- *Requirement 2*: The time of Wi-Fi transmission must be less than 0.08 seconds, one-third of the time interval between two shots of the Raspberry Pi camera.
- *Verification 2*: Record the average Wi-Fi transmission time by recording the time when the remote cloud server returns the result and the time Arduino receives.

#### 2.2.3 Difficulty and Risk Analysis

Since the microcontroller links all other subsystems and components in this design, it is essential to avoid any potential misusing or misleading practices on the Arduino Uno R3.

#### 2.2.4 Tolerance Analysis

We use time to evaluate the performance of this subsystem. If the time of Wi-Fi transmission is less than 0.08 seconds and the time of UART transmission is also less than 0.08 seconds, we consider this subsystem to be successfully constructed and functioning.

#### 2.3 Thorough Image Analysis Subsystem

#### 2.3.1 Subsystem Overview

The main component in the *Thorough Image Analysis Subsystem* is the remote cloud server containing a powerful GPU to perform more complex and more accurate image analysis and object detection. When Wi-Fi signals are available, it can also take the responsibility of thorough image analysis to ensure the self-speed adjustment and obstacle detection of the autonomous vehicle. This subsystem is closely related to the *Microcontroller Subsystem* as the remote cloud server communicates with the microcontroller Arduino Uno R3 via Wi-Fi modules for image and speed/obstacle information transmissions.

#### 2.3.2 Acceptance Requirements

- Requirement 1: The accuracy of speed limit sign recognition must be larger than 80%.
- *Verification 1*: Generate images of different speed limits ranging from 0 to 30 km/h (according to the rules on the campus) to test the recognition algorithm on the remote cloud server and record the accuracy of recognition.
- *Requirement 2*: The time of speed limit sign recognition must be less than 0.08 seconds, one-third of the time interval between two shots of the Raspberry Pi camera.
- *Verification 2*: Generate images of different speed limits ranging from 0 to 30 km/h (according to the rules on the campus) to test the recognition algorithm on the remote cloud server and record the average recognition time.

#### 2.3.3 Difficulty and Risk Analysis

Since the computer vision algorithms implemented on the remote cloud server might be complex to enhance the accuracy of object and speed sign detection, finding and finetuning a powerful algorithm like Yolo v3 [3] to detect obstacles and speed limit signs while satisfying the time constraint of 0.08 seconds might take some time of careful consideration.

#### 2.3.4 Tolerance Analysis

We use accuracy and time to evaluate the performance of this subsystem. If the time of speed limit sign recognition is less than 0.08 seconds and the accuracy of speed limit sign recognition is larger than 80%, we consider this subsystem to be successfully constructed and functioning.

#### 2.4 Microcontroller Subsystem

#### 2.4.1 Subsystem Overview

The main component in the *Microcontroller Subsystem* is the Arduino UNO R3. With a power supply of 5 volts direct current, it connects the components of the Raspberry Pi 4B, the remote cloud server, the robot arm, and the vehicle across all other subsystems. It enables simultaneous reading and writing via UART to receive information from the Raspberry Pi 4B in the *Image Capture and Simple Analysis Subsystem* and delivers it to the vehicle to adjust motor speed via PWM. It also enables Wi-Fi transmission with the remote cloud server in the *Thorough Image Analysis Subsystem* by controlling the Wi-Fi module.

#### 2.4.2 Acceptance Requirements

- *Requirement 1*: The time of UART transmission must be less than 0.08 seconds, one-third of the time interval between two shots of the Raspberry Pi camera.
- *Verification 1*: Record the average UART transmission time by recording the time when the Raspberry Pi 4B generates the result and the time Arduino receives.
- *Requirement 2*: The time of Wi-Fi transmission must be less than 0.08 seconds, one-third of the time interval between two shots of the Raspberry Pi camera.

• *Verification 2*: Record the average Wi-Fi transmission time by recording the time when the remote cloud server returns the result and the time Arduino receives.

#### 2.4.3 Difficulty and Risk Analysis

Since the microcontroller links all other subsystems and components in this design, it is essential to avoid any potential misusing or misleading practices on the Arduino Uno R3.

#### 2.4.4 Tolerance Analysis

We use time to evaluate the performance of this subsystem. If the time of Wi-Fi transmission is less than 0.08 seconds and the time of UART transmission is also less than 0.08 seconds, we consider this subsystem to be successfully constructed and functioning.

#### 2.5 Output Subsystem

#### 2.5.1 Subsystem Overview

The main component in the *Output Subsystem* is a 4-axis 4-degree robot arm and a vehicle with two DC motors. With a power supply of 12 volts direct current, both are controlled by the Arduino Uno R3 in the *Microcontroller Subsystem*. On receiving the clearing command from the Arduino Uno R3 via the Wi-Fi module, the robot arm picks up the obstacle via a vacuum suction cup and completes the obstacle-clearing task. If the command of speed adjustment is received via UART protocols, the vehicle adjusts the speed of its DC motors via PWM.

#### 2.5.2 Acceptance Requirements

- *Requirement 1*: The time of obstacle clearing by the robot arm must be less than 0.24 seconds, the time interval between two shots of the Raspberry Pi camera.
- Verification 1: Record the obstacle picking and clearing time.

#### 2.5.3 Difficulty and Risk Analysis

Since the vehicle carries all other subsystems and components in this design, it is essential to avoid any potential misusing or misleading practices on the DC motors.

## 2.5.4 Tolerance Analysis

We use time to evaluate the performance of this subsystem. If the time of obstacle clearing is less than 0.24 seconds, we consider this subsystem to be successfully constructed and functioning.

## 3 Ethics and Safety

#### 3.1 Ethical Issues

For the privacy part, image capturing might inevitably incorporate students' faces, which requires us to manually blur or remove such private information to protect students. For the social effects, the introduction of autonomous cleaning vehicles might reduce the needs of cleaning staff on the campus, which requires us to collaborate with campus administration to reassign affected staff to other roles or help them become the technical controller of such autonomous vehicles [2, 4].

### 3.2 Safety Issues

Since this autonomous vehicle is under testing, it might cause some injuries or destroy to the students or the buildings if it is out of control, which requires our designers to watch it carefully when testing and preemptively identify and mitigate potential hazards [5].

## References

- [1] Ross Girshick. Fast r-cnn. In *Proceedings of the IEEE international conference on computer vision*, pages 1440–1448, 2015.
- [2] Andreia Martinho, Nils Herber, Maarten Kroesen, and Caspar Chorus. Ethical issues in focus by the autonomous vehicles industry. *Transport reviews*, 41(5):556–577, 2021.
- [3] Joseph Redmon and Ali Farhadi. Yolov3: An incremental improvement. *arXiv preprint arXiv:1804.02767*, 2018.
- [4] Hong Wang, Amir Khajepour, Dongpu Cao, and Teng Liu. Ethical decision making in autonomous vehicles: Challenges and research progress. *IEEE Intelligent Transportation Systems Magazine*, 14(1):6–17, 2020.
- [5] Jun Wang, Li Zhang, Yanjun Huang, and Jian Zhao. Safety of autonomous vehicles. *Journal of advanced transportation*, 2020(1):8867757, 2020.